




CONFLARE BRUSHES

Conflare and square wheel brushes are mounted on a 1/4" shank to provide quick and easy installation in a collet or chuck. Note: Brushes must be fully inserted in chuck and tightened securely! Available in high carbon steel or stainless steel for aggressive cutting action.

CONFLARE BRUSH - 1/4 Shank



CATALOG NUMBER		Diameter	Wire Size	Face Width	M.S.F.S. (R.P.M.S.)
H/C Steel	Stainless				
76000	76002	1-1/2"	.006	1/2"	20000
76004		1-1/2"	.008	1/2"	20000
76006		1-1/2"	.0104	1/2"	20000
76008	76010	1-1/2"	.0118	1/2"	20000
76012	76014	2"	.006	3/8"	20000
76016	76018	2"	.008	3/8"	20000
76020	76022	2"	.0104	3/8"	20000
76024	76026	2"	.0118	3/8"	20000
76028	76030	2"	.014	3/8"	20000
76032		2"	.020	3/8"	20000
76034	76036	2-1/2"	.006	3/8"	20000
76038	76040	2-1/2"	.008	3/8"	20000
76042	76044	2-1/2"	.0104	3/8"	20000
76046	76048	2-1/2"	.0118	3/8"	20000
76050	76052	2-1/2"	.014	3/8"	20000
76054		2-1/2"	.020	3/8"	20000
76056	76058	3"	.006	3/8"	20000
76060	76062	3"	.008	3/8"	20000
76064	76066	3"	.0104	3/8"	20000
76068	76070	3"	.0118	3/8"	20000
76072	76074	3"	.014	3/8"	20000
76076		3"	.020	3/8"	20000



ALWAYS OBSERVE THE FOLLOWING SAFETY PRACTICES • Never operate Rotary Brushes above recommended safe speed • Keep all machine guards in place during operation • Always wear protective eye goggles when working.